2012

KLX™ 250S

Kawasaki

DUAL PURPOSE

When the pavement ends, the fun doesn't have to stop when you're riding the Kawasaki KLX250S. All you need to ride on the street are lights and turn signals but the KLX250S's heart belongs in the dirt. With its 249cc liquid-cooled single, long-travel suspension and rugged steel frame, this lightweight machine lets you access the best of both worlds.


For more information visit kawasaki.ca/12klx250s



Fuel Efficient

Vehicles that have a fuel efficiency rating under 5.5L/100km

FIRECRACKER RED†









1 | Compact 249cc liquid-cooled DOHC engine design is lightweight and high revving, with a broad torque curve.

2 | Multi-function digital instrumentation.

3 | Quick and easy push-button electric starting.

4 | Lightweight dual high-capacity Denso radiators deliver superior cooling efficiency and contribute to space and weight savings.

5 | KLX-spec handlebar for a more relaxed position and effortless control.

- Good mass centralisation for superior handling and a tubular-section high-tensile steel perimeter frame for a slim, lightweight package.

2012 KLX™ 250S

DUAL PURPOSE

LIME GREEN†



ACCESSORIES

1. Wheel Chock
2. Steadymate Cinchtite Tie Down Straps
3. Soft Loop
4. Work Pad



† Canadian model may not be exactly as shown

Engine type	4-stroke, DOHC, 4-valve single
Displacement	249cc
Bore x stroke	72.0 x 61.2 mm
Cooling	Liquid, twin radiators
Fuel system	Keihin CVK34 carburettor
Compression ratio	11.0:1
Ignition	Digital DC-CDI
Starting	Electric
Transmission	6-speed
Final drive	Sealed Chain
Frame	Perimeter, high-tensile steel
Rake/trail	26.5°/105 mm (4.1 in.)
Suspension / front wheel travel	43 mm inverted cartridge fork with 16-way compression and rebound damping adjustment/255 mm (10.0 in.)
Suspension / rear wheel travel	UNI-TRAK® with adjustable preload, 16-way compression and rebound damping adjustment/230 mm (9.1 in.)
Tire, front/rear	3.00-21, 4.60-18
Brakes, front	250 mm semi-floating petal disc with dual-piston hydraulic caliper
Brakes, rear	240 mm petal disc with single-piston hydraulic caliper
Wheelbase	1430 mm (56.3 in.)
Seat height	890 mm (35 in.)
Ground clearance	285 mm (11.2 in.)
Curb mass*	135 kg (297.5 lbs.)
Fuel capacity	7.7 litres (1.7 gal.)
Colours	Firecracker Red or Lime Green
Warranty	12 months

* Includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90% of capacity) and tool kit (if supplied)

SAFE RIDING'S MORE FUN

Ride responsibly. Kawasaki believes safety begins with us and continues with you. Always wear a helmet, eye protection, and proper apparel. Never ride under the influence of drugs or alcohol. Riding is more fun on a well-maintained motorcycle...follow the instructions in your owner's manual. Remember, riding safe is smart.

Take an in-depth tour @ kawasaki.ca/12klx250s

View our complete accessory catalogue @ kawasaki.ca/accessories

Kawasaki subscribes to the guidelines of Tread Lightly!, a program dedicated to protecting the great outdoors through education and fostering responsible enjoyment of public lands.








EXTEND YOUR FACTORY PROTECTION

Kawasaki

The specifications mentioned here apply to and have been achieved by production models under standard operating conditions. We intend only to give a fair description of the vehicle and its performance capabilities but these specifications may not apply to every machine supplied for sale. Kawasaki Heavy Industries, Ltd. reserves the right to alter specifications without prior notice. Equipment illustrated and specifications may vary to meet individual markets. Available colours may vary by market.



99969-2633E